



## PATENT ABSTRACTS OF JAPAN

(11) Publication number: **2001070797 A**(43) Date of publication of application: **21.03.01**

(51) Int. Cl.

**B01J 29/22****B01D 53/94****B01J 29/24**(21) Application number: **11248663**(22) Date of filing: **03.09.99**(71) Applicant: **MITSUBISHI ELECTRIC CORP**(72) Inventor:  
**MITSUBA KENRO**  
**SATO MINORU**  
**KATASHIBA HIDEAKI**  
**OUCHI YASUSHI****(54) ELECTROCHEMICAL CATALYST FOR EXHAUST GAS PURIFICATION****(57) Abstract**

**PROBLEM TO BE SOLVED:** To provide an exhaust gas purifying catalyst which dispenses with frequent switching to a rich atmosphere, which frequent switching is necessary for the conventional exhaust gas purifying catalyst, because the conventional catalyst carries out oxidation reactions and reduction reactions on the same catalyst particles at the same time, so that, when operated in a lean atmosphere, a rich mode to temporally switch to a lean atmosphere must be often performed to reduce NO<sub>x</sub>.

**SOLUTION:** This catalyst is formed by mixing a catalyst A 1 comprising a NO<sub>x</sub> absorbing substance and a NO<sub>x</sub> reducing catalyst, a catalyst B 2 comprising a hydrocarbon adsorbing substance and a hydrocarbon oxidizing catalyst, and a mixture 3 of an electron conductive substance C and an ion conductive substance D. Electrons are moved between the catalyst A 1 and the catalyst B 2 through the electron conductive substance C, and ions are moved through the ion conductive substance D. Electrochemical reduction reactions in the catalyst A 1 and electrochemical oxidation reactions in

the catalyst B 2 progress separately, and the reduction of the adsorbed NO<sub>x</sub> is promptly carried out by using the adsorbed hydrocarbon regardless of atmosphere.

COPYRIGHT: (C)2001,JPO

